

IN THE CLAIMS:

Please amend the claims to read as follows:

1. (Currently Amended) An inspection coaxial probe, comprising:

a conductive block, formed with a first face, a second face and a through hole connecting the first face and the second face;

a contact probe, comprising:

a conductive pipe; and

a conductive plunger, retractably provided in at a first end of the pipe, the plunger being to be brought into contact with a device to be inspected; and

a first retainer, comprising a first insulative member ~~through which~~ that retains the first end of the pipe ~~is retained~~ in the vicinity of the first face of the block, such that the pipe is coaxially held within the through hole ~~while forming a gap between~~ and such that an outer periphery of a part of the pipe ~~and~~ directly opposes an interior wall of the through hole while forming an air gap therebetween.
2. (Original) The inspection coaxial probe as set forth in claim 1, wherein:

the first insulative member is a substrate provided on the first face of the block, and formed with a recess and a through hole communicated with the recess; and

the first end of the pipe is fitted into the recess such that the plunger coaxially extends through the through hole of the substrate.

3. (Original) The inspection coaxial probe as set forth in claim 1, wherein:

a first end portion of the through hole of the block is narrowed;

the first insulative member is a spacer formed with a recess and a through hole communicated with the recess; and

the first insulative member is inserted into the first end portion of the through hole and the first end of the pipe is fitted into the recess, such that the plunger coaxially extends through the through hole of the spacer and the through hole of the substrate.

4. (Original) The inspection coaxial probe as set forth in claim 1, further comprising a conductive plate, formed with a first recess and a first through hole communicated with the first recess, the plate being provided on the first face of the block, wherein:

the first insulative member is a spacer formed with a second recess and a second through hole communicated with the second recess; and

the first insulative member is inserted into the first recess and the first end of the pipe is fitted into the second recess, such that the plunger coaxially extends through the first through hole, the second through hole and the through hole of the block.

5. (Original) The inspection coaxial probe as set forth in claim 1, further comprising a second retainer, comprising a second insulative member through which a second end of the pipe is retained in the vicinity of the second face of the block,

wherein the contact probe is electrically connected to a wiring board on which an inspection circuit is provided via the second end of the pipe.

6. (Original) The inspection coaxial cable as set forth in claim 5, wherein:

a first recess is formed on the second face of the block;

the second insulative member is a spacer formed with a second recess and a through hole communicated with the second recess;

the spacer is fitted into the first recess and the second end of the pipe is fitted into the second recess, such that the second end of the pipe is electrically connected to the wiring board via the through hole of the spacer, while the spacer is held by the wiring board within the first recess.

7. (Original) An apparatus for inspecting an electrical characteristic of a device, the apparatus comprising:

the inspection coaxial probe as set forth in claim 1; and

a wiring board, on which an inspection circuit is provided, and to which a second end of the pipe is electrically connected.

8. (Previously Presented) The inspection coaxial probe as set forth in claim 1, wherein the contact probe further comprises a spring inserted in the conductive pipe to force the conductive plunger outwardly.